

Data Sheet

Type Number 20344
Designation IEC SR 42
System Silver oxide / Zinc /
NaOH - Electrolyte



Nominal Voltage 1,55 V
Typical Capacity C 100 mAh
Load 5,6 kOhm, at 20°C down to 1.2 V

Weight (approx.) 1,49 g
Volume 0,38 ccm
Coding..... Date of Manufacturing
Month / Year

Temperature Ranges	min	max.
Storage	-10 °C	65 °C
Discharge	-10 °C	65 °C

Dimensions	min	max.
Diameter (Ø).....	11,25	11,6
Height (A/B)	3,3	3,6

Segment Watch

Main Applications Watch
Photo
Electronic

Typical Capacities (at 20 °C)

Discharge Type	Load	End Voltage:	1.2 V
Continuous	5600 Ω	Time:	365
24h/d, 7d/w		Capacity [mAh]:	100
Current [µA]:	275	Energy [mWh]:	155

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst

Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!

Date of issue: 2012-04-12