V 371 HC MF

Mercury - free

Primary Silver

Data Sheet



Type Number	30371
Designation IEC	SR 69
System	Silver oxide / Zinc / KOH - Electrolyte
Nominal Voltage	1,55 V
Typical Capacity C	42 mAh
Load 20 kOhm, at 20°C down to 1.2 V	
Weight (approx.)	0,61 g
Volume	0,14 ccm
Coding	Date of Manufacturing Month / Year

Temperature Ranges	min	max.
Storage	-10°C	65°C
Discharge	-10°C	65°C

Dimensions	min	max.
Diameter (∅)	9,25	9,5
Height (A/B)	1,85	2,1

Segment ..... Watch

Typical Capacities (at 20°C)

Discharge Type	**Load**	**End Voltage:**	**1.2 V**
Continuous 24h/d,7d/w	20000 Ω	Time:	530 h
		Capacity [mAh]:	42
		Energy [mWh]:	65

All Data contained herein is for single cells
For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!

Date of issue: 2012-04-12